

SUPPORTED DEVICES/APPLICATIONS

SOURCE	APPLICATION
DVI, HD-SDI	HD Endoscopy, PACS, Vital Signs, Room Camera
HD-RGBS, HD-YP _b P _r	HD Endoscopy
RGBS, YP _b P _r , SDI	SD Endoscopy
S-Video, Composite	Fluoroscopy, SD Endoscopy, Ultrasound
VGA	PACS, Ultrasound, Angiography, Vital Signs

IMAGE PERFORMANCE

LCD Panel	Active Matrix TFT LCD, LED Backlight
Picture Size (W x H)	12.0 x 9.0 inches (304 x 228 mm)
Viewing Area (Diagonal)	15 inches (381 mm)
Pixel Pitch	0.297 mm
Resolution (H x V)	1024 x 768 (XGA)
Luminance	350 cd/m ²
Contrast Ratio	1500:1
Aspect Ratio	4:3
Number of Colors	16.8 Million
Viewing Angle	170°
Response Time	14 ms (typical)
Gamma	1.8, 2.0, 2.2, 2.4, 2.6, VIDEO, PACS (DICOM)

GENERAL

Input Power Requirements	22 – 24 Volts DC
Power Consumption	23W (typical)
Dimensions (W x H x D)	15.2 x 11.9 x 3.2 inches (386 x 302 x 81 mm)
Weight	7.1 lbs (3.3Kg)
Temperature	Operating: 0 to +40°C (+32 to +104°F) Storage: -20 to +50°C (-4 to +122°F)
Humidity	Operating: 20 – 85% RH Storage: 10 – 90% RH
Mounting	100 mm VESA

STANDARD DISPLAY PART NUMBER

90K0015 - 15" EndoVue® HD LED

VIDEO INPUT FORMATS

Format	Input (Digital)	Input (Analog)	Horizontal Frequency (kHz)
576/50i (PAL)	SDI	Comp, S-Video, RGBS, YP _b P _r	15.625
480/60i (NTSC)	SDI	Comp, S-Video, RGBS, YP _b P _r	15.734
576/50p	DVI	RGBS, YP _b P _r	31.250
480/60p	DVI	RGBS, YP _b P _r	31.469
720/50p	HD-SDI, DVI	HD-RGBS, HD-YP _b P _r	37.500
720/60p	HD-SDI, DVI	HD-RGBS, HD-YP _b P _r	45.000
1080/50i	HD-SDI, DVI	HD-RGBS, HD-YP _b P _r	28.125
1080/60i	HD-SDI, DVI	HD-RGBS, HD-YP _b P _r	33.750
1080/50p	DVI	--	56.2
1080/60p	DVI	--	67.3

HIGH DEFINITION LED BACKLIGHT SURGICAL DISPLAY



INPUTS

DVI	DVI-D
HD-SDI	BNC, 75 Ω
HD-RGBS, RGBS	DVI-I or HD-15, 0.7 Vp-p ± 6db, 75 Ω
HD-YP _b P _r / YP _b P _r	DVI-I or HD-15, 0.7 Vp-p ± 6db, 75 Ω
VGA	HD-15, 0.7 Vp-p ± 6db, 75 Ω
S-Video	DIN-4, 0.7 Vp-p +6/-3db, 75 Ω
Composite	BNC, 0.7 Vp-p +6/-3db, 75 Ω

CONNECTIVITY

DC OUTPUT

5 Volts DC Output	Mating Power Plug - CUI P/N PP-015 (Up to 1 Amp) (For powering an external fiber-optic receiver)
-------------------	---

CONTROL INPUT

Serial Remote	D-sub 9pin, RS-232C
ND-OS	Mini-USB

USER CONTROLS - ON-SCREEN MENU

Input Selection, Brightness, Contrast, Hue, Saturation, Gamma, Sharpness, RGB Gain, Backlight Level, Horizontal & Vertical Position, Phase, Frequency, DPMS, Auto-Source Select, Scaling, Overscan, Programmable User / Modality Settings Profiles


SUPPLIED/OPTIONAL ACCESSORIES

Supplied: Power Supply, AC Cord, Video Cables - S-Video, BNC, VGA, DVI, Product Documentation CD, Printed User Manual

Optional: Desktop Stand (P/N 26B0083) 30 ft. Power Extension Cable Kit (90I0017), 5 VDC Output Cable For Fiber Adapter (35X0100)

COMPLIANCE & CERTIFICATIONS ANSI/AAMI ES60601-1, CAN/CSA C22.2 No. 60601-1, FCC Class B, EN60601-1, EN60601-1-2, CE, IP 32 (Pending), MDD 93/42/EEC, 2007/47/EC, RoHS, WEEE, Class I Medical Device.

INPUT / OUTPUT CONNECTOR PANEL



Corporate Headquarters

5750 Hellyer Avenue
San Jose, CA 95138 (USA)
Tel: 408 776 0085
Toll Free: 866 637 5237
Email: info@endssi.com

Europe

Nijverheidscentrum 28
2761 JP Zevenhuizen (ZH)
The Netherlands 
Tel: +31 180 63 43 56
Email: info-EMEA@endssi.com

Asia Pacific

East Square Omori,
6-20-14 Minamioi, Shinagawa-ku,
Tokyo 140-0013, Japan
Tel: +81 3 5753 2466
Email: info@endssi.jp