## MaxO<sub>2</sub>Vent<sup>™</sup>

- Time cycled and inspiratory flow variable
- Single circuit
- Volume consistent
- Pneumatically powered
- 5 year warranty



## **A Portable Pneumatic Ventilator**

The MAXO<sub>2</sub>Vent<sup>™</sup> is MRI compatible, low cost and is smaller than a toaster, making it great for transport. Includes patient tubing circuit and manifold with exhalation diaphragm.

## **Specifications**

Dimensions	7" x 5" x 4"
Weight	4.5 lbs
Case Material	Aluminum
All other Materials	Aluminum, brass and plastic
Gas Inlet Pressure Range	30 to 150 PSI
Expiratory Time Range	0.2 to 60 seconds
Ispiratory Time Range	0.2 to 3.0 seconds
Tidal Volume Range	0 to 2.0 L
Pressure Relief Range	0 to 120 CMH20
IMV/CPAP Continuous Flow Range	0 to 60 LPM
PEEP/CPAP Range	+1 to +50 CMH <sub>2</sub> O
Internal Compliance	0 CMH <sub>2</sub> O
Air/Oxygen Blenders	Any capable of producing from 30 to 60 PSI
Exhalation Valves	Oceanic-P/N 15.0 reusable
Warranty	Five year unconditional

## **Part Numbers**

MAXO <sub>2</sub> Vent <sup>™</sup>	Exhalation Patient Tubing
Exhalation Valve Diaphragm	IPPB Bird ManifoldR100P07
Reusable Peep Valve	<b>15' Single Coiled Hose</b>
Pole Mount R100P03	-

maxtec